

FCC TEST REPORT

On Behalf of

Product Name: Pet Grooming Clipper

Trademark: Wadisino

Model Number: 1000801

Prepared For: Shanghai Wald Industrial Co., Ltd

Address: No. 3, Lane 1800, Xin Songjiang Road, Songjiang District, Shanghai

Prepared By: Shenzhen Huaxiang Testing Co , Ltd

Address: 1st Floor, Building A1, No. 2082 Jincheng Road, Shajing Street, Bao'an District, Shenzhen City, Guangdong Province China

Report No.: HUAX251104417KR

TABLE OF CONTENTS

Description	Page
The Report Description	
1 GENERAL INFORMATION	4
1.1. Description of Device (EUT)	4
1.2. Description of test facility	4
1.3. Test Standards	4
1.4. Test Summary	5
1.5. Measurement Uncertainty	5
2. POWER LINE CONDUCTED MEASUREMENT	6
2.1. Test Equipment	6
2.2. Block Diagram of Test Setup	6
2.3. Power Line Conducted Emission Measurement Limits (Class B)	6
2.4. Configuration of EUT on Measurement	7
2.5. Operating Condition of EUT	7
2.6. Test Procedure	7
2.7. Power Line Conducted Emission Measurement Results	7
3. RADIATED EMISSION MEASUREMENT	8
3.1. Test Equipment	8
3.2. Block Diagram of Test Setup	8
3.3. Radiated Emission Limit (Class B)	9
3.4. EUT Configuration on Measurement	9
3.5. Operating Condition of EUT	10
3.6. Test Procedure	10
3.7. Radiated Emission Measurement Results	10
 APPENDIX I (Photos of EUT)	

TEST REPORT DECLARATION

Applicant	:	Shanghai Wald Industrial Co., Ltd
Address :	:	No. 3, Lane 1800, Xin Songjiang Road, Songjiang District, Shanghai
Manufacturer:	:	Shanghai Wald Industrial Co., Ltd
Address :	:	No. 3, Lane 1800, Xin Songjiang Road, Songjiang District, Shanghai
EUT Description :	:	Pet Grooming Clipper
Model Number	:	1000801
Rating(s)	:	DC 5V, 1.5A, 7.5W
Test Date	:	Nov. 03, 2025 - Nov. 10, 2025
Date of Report	:	Nov. 10, 2025

Test Standards:

FCC Part 15 subpart B Class B (2017)

The EUT described above is tested by US to determine the maximum emission levels emanating from the EUT, the maximum emission levels are compared to the FCC Part 15 limits. The measurement results are contained in this test report. and Shenzhen Huaxiang Testing Co , Ltd. is assumed of full responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT is to be technically compliant with the FCC requirements

This report applies to above tested sample only and shall not be reproduced in part without written approval of Shenzhen Huaxiang Testing Co , Ltd.

Prepared by(Test Engineer):

Kevin Su

Kevin Su

Amy Jiang

Amy Jiang

Approved(Manager)

1 GENERAL INFORMATION

1.1. Description of Device (EUT)

EUT	:	Pet Grooming Clipper
Model Number	:	1000801
Supplementary Model	:	/
Test Voltage	:	DC 5V
Applicant	:	Shanghai Wald Industrial Co., Ltd
Address	:	No. 3, Lane 1800, Xin Songjiang Road, Songjiang District, Shanghai
Manufacturer	:	Shanghai Wald Industrial Co., Ltd
Address	:	No. 3, Lane 1800, Xin Songjiang Road, Songjiang District, Shanghai

1.2. Description of test facility

All measurement required was performed at laboratory of Shenzhen Huaxiang Testing Co , Ltd at 1st Floor, Building A1, No. 2082 Jincheng Road, Shajing Street, Bao'an District, Shenzhen City, Guangdong Province China

Shenzhen Huaxiang Testing Co , Ltd EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission.

1.3. Test Standards

The following Declaration of Conformity report of EUT is prepared in accordance with 47CFR Part 15(2014): Radio Frequency Device: Subpart B; Unintentional radiators Class B

ANSI C63.4 (2019): Interim Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9KHz to 40GHz.

1.4. Test Summary

TEST ITEMS	RESULT	NOTE
Disturbance voltage at a.c. mains terminal	PASS	
Radiated emission	PASS	

Notes: N/A=Not Applicable

1.5. Measurement Uncertainty

Radiation Uncertainty : $U_r = \pm 3.84\text{dB}$

Conduction Uncertainty : $U_c = \pm 2.72\text{dB}$

2. POWER LINE CONDUCTED MEASUREMENT


2.1. Test Equipment

The following test equipments are used during the power line conducted measurement:

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Test Receiver	Rohde & Schwarz	ESCS30	8289851018	Nov. 20, 2024	1 Year
2.	L.I.S.N.	Rohde & Schwarz	ESH2-Z5	834549/005	Nov. 20, 2024	1 Year
3.	Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100006	Nov. 20, 2024	1 Year
4.	RF Cable	FUJIKURA	RG-55/U	LISN Cable	Nov. 20, 2024	1 Year


2.2. Block Diagram of Test Setup

2.2.1 Block diagram of connection between the EUT and simulators



(EUT: Pet Grooming Clipper)

2.2.2 Block diagram of test setup



(EUT: Pet Grooming Clipper)

2.3. Power Line Conducted Emission Measurement Limits (Class B)

Frequency MHz	Limits dB(μV)	
	Quasi-peak Level	Average Level
0.15 ~ 0.50	66 ~ 56*	56 ~ 46*
0.50 ~ 5.00	56	46
5.00 ~ 30.00	60	50

Notes: 1. *Decreasing linearly with logarithm of frequency.

2. The lower limit shall apply at the transition frequencies.

2.4. Configuration of EUT on Measurement

The following equipments are installed on Power Line Conducted Emission Measurement to meet the commission requirement and operating regulations in a manner, which tends to maximize its emission characteristics in a normal application.

EUT : Pet Grooming Clipper
Model Number : 1000801

2.5. Operating Condition of EUT

2.5.1. Setup the EUT and simulator as shown as Section 2.2.

2.5.2. Turn on the power of all equipment.

2.5.3. Let the EUT work in test mode (Normal) and measure it.

2.6. Test Procedure

The EUT system is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides 50ohm-coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs. Both sides of AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to FCC/ANSI C63.4-2009 on Conducted Emission Measurement.

The bandwidth of test receiver (R & S ESCS30) is set at 9KHz.

The frequency range from 150KHz to 30MHz is checked.

The test result is reported on Section 2.7.

The frequency range from 150KHz to 30 MHz is investigated.

2.7. Power Line Conducted Emission Measurement Results

N/A

3. RADIATED EMISSION MEASUREMENT

3.1. Test Equipment


The following test equipments are used during the radiated emission measurement:

3.1.1. For Anechoic Chamber

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Spectrum Analyzer	ANRITSU	MS2661C	6200140915	Nov. 20, 2024	1 Year
2.	Test Receiver	Rohde & Schwarz	ESCS30	828985/018	Nov. 20, 2024	1 Year
3.	Bilog Antenna	Schwarzbeck	VULB9163	142	Nov. 20, 2024	1 Year
4.	50 Coaxial Switch	Anritsu Corp	MP59B	6100237248	Nov. 20, 2024	1 Year
5.	Cable	Schwarzbeck	AK9513(1m)	CR RX2	Nov. 20, 2024	1 Year
6.	Cable	Schwarzbeck	AK9513(10m)	AC RX1	Nov. 20, 2024	1 Year
7.	Cable	Rosenberger	N/A(6m)	CR RX1	Nov. 20, 2024	1 Year
8.	Cable	Rosenberger	N/A(10m)	FP2RX2	Nov. 20, 2024	1 Year
9.	DC Power Filter	MPE	23872C	N/A	Nov. 20, 2024	1 Year
10.	Single Phase Power Line Filter	MPE	23332C	N/A	Nov. 20, 2024	1 Year
11.	3 Phase Power Line Filter	MPE	23333C	N/A	Nov. 20, 2024	1 Year
12.	Signal Generator	HP	8648A	3625U00573	Nov. 20, 2024	1 Year


3.2. Block Diagram of Test Setup

3.2.1. Block diagram of connection between the EUT and simulators



(EUT: Pet Grooming Clipper)

3.2.2. Anechoic Chamber Test Setup Diagram



3.3. Radiated Emission Limit (Class B)

FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		$\mu\text{V/m}$	$\text{dB}(\mu\text{V})/\text{m}$
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0

Remark: (1) Emission level $(\text{dB})\mu\text{V} = 20 \log \text{Emission level } \mu\text{V/m}$
 (2) The smaller limit shall apply at the cross point between two frequency bands.
 (3) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.

3.4. EUT Configuration on Measurement

The following equipment are installed on Radiated Emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

Pet Grooming Clipper(EUT)

Model Number : 1000801

3.5. Operating Condition of EUT

1. Setup the EUT as shown in Section 3.2.
2. Let the EUT work in test mode (Normal) and measure it.

3.6. Test Procedure

EUT and its simulators are placed on a turntable, which is 0.8 meter high above ground. The turntable can rotate 360 degrees to determine the position of the maximum emission level. EUT is set 3.0 meters away from the receiving antenna, which is mounted on an antenna tower. The antenna can be moved up and down between 1.0 meter and 4 meters to find out the maximum emission level. Broadband antenna (calibrated bilog antenna) is used as receiving antenna. Both horizontal and vertical polarization of the antenna is set on measurement. In order to find the maximum emission levels, all of the interface cables must be manipulated according to ANSI C63.4-2009 on radiated emission measurement. The bandwidth of the EMI test receiver (R&S ESCS30) is set at 120KHz.

The frequency range from 30MHz to 1000MHz is investigated.

3.7. Radiated Emission Measurement Results


PASS

Please reference to the following pages

Radiated emissions were conducted in charging mode and discharging mode and the worst case (discharging mode) was reported only.

Radiated Emission Test Data


EUT: Pet Grooming Clipper
M/N: 1000801
Operating Condition: Normal work
Test Site: 3m CHAMBER
Operator: Mark
Test Specification: /
Comment: Polarization: Horizontal



Suspected Data List											
NO.	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Det	Pol	Verdict
1	38.7387	33.76	18.50	-15.26	40.00	21.50	100	0	PK	Hori	PASS
2	55.2452	29.55	13.64	-15.91	40.00	26.36	100	58	PK	Hori	PASS
3	84.3744	30.51	11.46	-19.05	40.00	28.54	100	94	PK	Hori	PASS
4	145.5455	27.11	11.85	-15.26	43.50	31.65	100	0	PK	Hori	PASS
5	901.9319	36.36	30.80	-5.56	46.00	15.20	100	206	PK	Hori	PASS
6	953.3934	34.06	29.12	-4.94	46.00	16.88	100	4	PK	Hori	PASS

Radiated Emission Test Data

EUT: Pet Grooming Clipper
M/N: 1000801
Operating Condition: Normal work
Test Site: 3m CHAMBER
Operator: Mark
Test Specification: /
Comment: Polarization: Vertical



Suspected Data List											
NO.	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Det	Pol	Verdict
1	37.7678	33.72	18.95	-14.77	40.00	21.05	100	136	PK	Hori	PASS
2	56.2162	31.79	15.88	-15.91	40.00	24.12	100	38	PK	Hori	PASS
3	119.3293	34.57	17.53	-17.04	43.50	25.97	100	311	PK	Hori	PASS
4	162.0521	27.61	12.48	-15.13	43.50	31.02	100	177	PK	Hori	PASS
5	320.3203	27.53	12.16	-15.37	46.00	33.84	100	199	PK	Hori	PASS
6	953.3934	33.39	28.45	-4.94	46.00	17.55	100	202	PK	Hori	PASS

APPENDIX I (PHOTOS OF EUT)

FIGURE
GENERAL APPEARANCE OF EUT




Photo 1



Photo 2



Photo 3



Photo 4




Photo 5



Photo 6




Photo 7




Photo 8




Photo 9




Photo 10



Photo 11

*****THE END OF REPORT*****